

RAINWATER.
REINVENTED.

INTELLIGENT RAINWATER LIVING

Intelligent Rainwater Living

Designed for:

- Homes
- Installers
- Architects

- 

Silent.
- 

Reliable.
- 

Compact.




DELIRAIN MINI

APPLICATIONS




TOILETS



WASHING MACHINES



IRRIGATION



UTILITY CLEANING

ENGINEERING INSIDE



- 

SILENT

Designed for quiet operation.
- 

RELIABLE

Automatic switching between rainwater and mains water.
- 

COMPACT

Premium engineering in a remarkably compact footprint.

TECHNICAL SPECIFICATIONS

Maximum flow rate	80 l/min
Maximum head	50 m
Pressure range	1 - 5 bar
Maximum service pressure	5 bar
Maximum service pressure of the mains water pipe	4 bar
Power supply	230 V / 50 Hz
Protection class	IPX4
Maximum liquid temperature	35 °C
Maximum ambient temperature	50 °C
Maximum suction depth	6 m
Noise level	45 dB
Water type	Clean, free of solid or abrasive substances, not viscous, not aggressive, not crystallized and not chemically neutral.

Diameter of the rainwater pipe	1" BSP
Diameter of the mains water pipe	3/4" BSP
Diameter of the household pipes	1" BSP
Minimum load capacity of the wall	60 kg
Dimensions	44 cm D × 67 cm H × 64 cm W